

PRODUCT SPECIFICATION



Gloss White Polyester (IDP) Super removable 'cling' adhesive



Description

Stabilised white gloss finish polyester film. Waterproof and tear resistant for durable long life labelling.

Adhesive

Super removable acrylic emulsion 'cling' adhesive.
Minimum application temperature: +5°C
Temperature range: -7°C to +50°C
This super removable adhesive sticks to glass, paint, metal or any smooth, dry, non porous surfaces. It removes cleanly leaving no residue and is excellent for surfaces requiring regular cleaning (e.g. washrooms, display surfaces, tiles, mirrors) as it can be re-applied. Unlike other materials available that rely on static attraction to the surface this very special adhesive means that materials can be die cut into labels.
Approved for indirect contact on dry and 'moist' non-fatty foods.
The product complies with BSEN 71-3:1995 Incorporating Amendment No 1 (European Standard on safety of toys)
No heavy metals are used in the manufacturing process and typical contents are less than 1 ppm.

Backing

Stabilised coated polyester to give maximum stability to the laminate.

Printing Information

Litho:

Use fully oxidising inks formulated for use on polyester grades. Remove all traces of oil based inks and varnishes from ink delivery system. Wherever possible print 4 colours in one pass and run press as dry as possible. Use spray powder sparingly as it will retard drying. Die cut labels - use formulated extra low tack inks (not just reduced) and a hard blanket (compressibles are not advised as they increase the suction effect on the labels).

Laser & Copier - 'digital':

Excellent laser printing results.
To reduce static it is advisable to build the feed stack sheet by sheet to introduce an air layer - keep stacks small and only load when ready to print.
For best results set paper type as Plain and media weight appropriate to the laminate.

Ink Jet:

Not suitable for aqueous based ink jet

HP Indigo:

Approved for HP Indigo printing.

Laminate:

Thickness: 140mic Weight: 190gsm

Availability

Available in ranges:
PCL3 Digital
A3
SRA3+
A similar product is also available in our A4 ranges - PCL and Digital Office.



Disclaimer: Technical information, statements and recommendations are given in good faith and are based on tests we believe to be reliable, but do not constitute a guarantee or warranty. We give no guarantee as to the suitability of the product for a specific application, this should be tested by the user. Samples available on request. Unless otherwise agreed in writing, we only accept liability within the scope of our General Terms and Conditions of Delivery and Payment. This specification sheet replaces all earlier ones. All information subject to change without notice.
© Label Connections Limited 2013. All rights reserved.
www.pcllabels.com
Tel: +44 1480 211222
sales@labelconnections.co.uk
File date: 05/2013