

# PRODUCT SPECIFICATION



## Satin Gold Permanent

### Description

85gsm woodfree, machine coated base with satin gold 'metallic' coating

### Adhesive

Aqueous acrylic emulsion adhesive.  
Minimum application temperature: +5°C  
Temperature range: -20°C to +100°C  
Chill grade - ideal for chilled food labelling.  
Good adhesion to cardboard and low energy (e.g. plastic bags) surfaces. Good 'all round' permanent adhesive.  
Approved for indirect food contact.  
The adhesive conforms to the EN71-3 (Toy Safety) & Packaging (Essential Requirements) Regulations.  
No heavy metals are used in the manufacturing process and typical contents are less than 1 ppm.

### Backing

White high density kraft paper with excellent lay flat properties

### Printing Information

#### Litho:

Treat as a coated paper.  
Die cut labels - use formulated extra low tack inks (not just reduced) and a hard blanket (compressibles are not advised as they increase the suction effect on the labels).

#### Laser & Copier - 'digital':

Although the material is safe for use in hot fusing toner printers, as it is a double coated surface please be aware of the potential for 'bubbles' in the surface on some very hot fusing machines. Please try a variety of media weight settings in the region of 130 - 160gsm to find the optimum setting for your own printer. There may also be issues with toner transfer/surface static on some toner print technologies e.g. LED technology. Please request samples for testing

#### Ink Jet:

Not suitable

#### HP Indigo:

Not suitable

#### Laminate:

Thickness: 170 mic      Weight: 160gsm

### Availability

Available in ranges:

PCL  
Digital Office  
A4+  
A3  
SRA3  
SRA3+



**Disclaimer:** Technical information, statements and recommendations are given in good faith and are based on tests we believe to be reliable, but do not constitute a guarantee or warranty. We give no guarantee as to the suitability of the product for a specific application, this should be tested by the user. Samples available on request. Unless otherwise agreed in writing, we only accept liability within the scope of our General Terms and Conditions of Delivery and Payment.  
This specification sheet replaces all earlier ones.  
All information subject to change without notice.  
© Label Connections Limited 2013. All rights reserved.  
www.pcllabels.com  
**Tel: +44 1480 211222**  
**sales@labelconnections.co.uk**  
File date: 05/2013