

PRODUCT SPECIFICATION



Satin Silver Permanent

Description

85gsm woodfree, machine coated base with satin silver 'metallic' coating

Adhesive

Aqueous acrylic emulsion adhesive.
Minimum application temperature: +5°C
Temperature range: -20°C to +100°C
Chill grade - ideal for chilled food labelling.
Good adhesion to cardboard and low energy (e.g. plastic bags) surfaces. Good 'all round' permanent adhesive.
Approved for indirect food contact.
The adhesive conforms to the EN71-3 (Toy Safety) & Packaging (Essential Requirements) Regulations.
No heavy metals are used in the manufacturing process and typical contents are less than 1 ppm.

Backing

White high density kraft paper with excellent lay flat properties

Printing Information

Litho:

Treat as a coated paper.
Die cut labels - use formulated extra low tack inks (not just reduced) and a hard blanket (compressibles are not advised as they increase the suction effect on the labels).

Laser & Copier - 'digital':

Although the material is safe for use in hot fusing toner printers, as it is a double coated paper please be aware of the potential for 'bubbles' in the surface on some very hot fusing machines. Please try a variety of media weight settings in the region of 130 - 160gsm to find the optimum setting for your own printer. There may also be issues with toner transfer/surface static on some toner print technologies e.g. LED technology. Please request samples for testing

Ink Jet:

Not suitable

HP Indigo:

Not suitable

Laminate:

Thickness: 170 mic Weight: 160gsm

Availability

Available in ranges:

PCL
Digital Office
A4+
A3
SRA3
SRA3+



Disclaimer: Technical information, statements and recommendations are given in good faith and are based on tests we believe to be reliable, but do not constitute a guarantee or warranty. We give no guarantee as to the suitability of the product for a specific application, this should be tested by the user. Samples available on request. Unless otherwise agreed in writing, we only accept liability within the scope of our General Terms and Conditions of Delivery and Payment. This specification sheet replaces all earlier ones. All information subject to change without notice.
© Label Connections Limited 2013. All rights reserved.
www.pcllabels.com
Tel: +44 1480 211222
sales@labelconnections.co.uk
File date: 05/2013