

Product Specification

Satin Gold Permanent



Description

Satin Gold

85gsm, woodfree, machine coated base paper with satin gold 'metallic' coating.

Available adhesives: PERMANENT

Adhesive

PERMANENT

Aqueous acrylic emulsion adhesive.

Minimum application temperature: +5°C

Temperature range: -20°C to +100°C

Chill grade - ideal for sandwich/chilled food labelling.

Designed for laminates in a wide range of applications. Very good heat resistance which enables trouble free performance in different hot fusing print processes. Good adhesion to cardboard and low energy (e.g. plastic bags) surfaces.

Good 'all round' permanent adhesive.

Approved for indirect food contact and direct contact on dry and moist non-fatty foods.

Backing

White high density kraft paper with excellent lay flat properties.

Printing Information

Litho:

Treat as a coated paper.

Die cut labels - use extra low tack inks (formulated - not reduced) and hard blanket.

Laser:

As the paper is a coated grade be aware of potential 'bubbles' in the top surface on some very hot fusing laser printers.

Set paper type as 'extra heavy weight' 170 - 180gsm.

Copier:

See laser.

Ink Jet:

Not suitable

Indigo:

Not suitable.

Availability

Available in ranges:

PCL™

A4+

Digital Office

SRA3

A3

Disclaimer:

Technical information, statements and recommendations are given in good faith and are based on tests we believe to be reliable, but do not constitute a guarantee or warranty. We give no guarantee as to the suitability of the product for a specific application, this should be tested by the user. Unless otherwise agreed in writing, we only accept liability within the scope of our General Terms and Conditions of Delivery and Payment.

This information sheet replaces all earlier ones. All information subject to change without notice.

© Label Connections Limited 2009. All rights reserved.

www.pclabels.com

File date: July 2009

